ME 333 Introduction to Mechatronics Quiz 5

1. You have configured a digital output pin as open drain, and you want this digital output to read 5V when it is high and 0V when it is low. Draw the external circuit connected to this digital output to allow this to happen. (2 pts)



2. Some digital inputs are equipped with internal pull-up resistors. Say you want to use a switch (drawn below) as input on a digital input with an internal pull-up resistor. You want the input to read high when the switch is open and low when the switch is closed. Complete the circuit diagram below. (2 pts)



 Explain what change notification is. (2 pts) Triggers an interrupt when pin value changes from High to low/low to high.

4. The PIC32 has five 16-bit counter/timers. Which timers can be combined to create a 32-bit timer? (4 points)

Timer 2+3 and Timer 4+5.

5. The 16-bit Timer 1 can have prescalers $N = 1, 8, 64, 256 (2^0, 2^3, 2^6, 2^8)$. What is the maximum number if input pulses (to the prescaler) Timer 1 can count before it rolls over? What should the value of the prescaler N and period register PR1 be to achieve this maximum? Feel free to use exponents in you answers. (4 pts)

a) (2^{8°}* 2¹⁶) or (65536[°]* 256) b) N = 2⁸, PR1 = 65535 or 2¹⁶ – 1

6. The output compare module OC5 is using Timer2 to help generated a 100 kHz 25% duty cycle PWM.

(a) Assuming Timer2 uses the 80 MHz PBCLK as input with a prescaler of N = 1, what is the value of PR2? (2 pts)

80000000 Hz / 100000 Hz = 800. Therefore PR2 = 799 (800 accepted) (b) What is the value of OC5RS? (2 pts) OC5RS = duty cycle * (PR2+1) = .25 * 800 = 200

7. Reading an analog input has two steps: sampling to acquire the voltage, and conversion to turn it into a value 0 to 1023. The conversion takes 12 CPU cycles. Explain what is happening during 10 of those cycles. (2 pts)

Binary search starting at 0b100000000 that compares the current estimate to V_{SHA} (Sample and Hold Amplifier).